



Healthcare Series LED HDTV

22" LED Model J22HE820 28" LED Model J28HE840 32" LED Model J32HE840 42" LED Model J42HE841



Bed 1/2/3 Limiter Compatible



Pillow Speaker Compatible Programming





Listed

Healthcare UL Commercial

Interface



Friendly



Replacement



SPECIFICATIONS

SPECIFICATIONS	
J22HE820 - 22" L	ED HDTV
Cabinet Color	flat black
Screen Size	21.5" diagonal
Display Resolution	1366 x 768
Brightness (typical)	300 cd/m ²
Viewing Angle	178° × 178°
Response Time (typic	
Broadcast System	NTSC/ATSC/QAM
Max Audio Output	2 x 2.5 W
Pro:Idiom	No
VESA Standard	100 mm x 100 mm
Power Supply	AC 100-240V 60Hz
Power Consumption	30 W
Standby Consumption	
TV w/o Stand (WxHxI	D) 21 x 14.1 x 1.9"
Set Weight	7.9 lbs.
Shipping Weight	11.2 lbs.

J28HE840 - 28" LED HDTV		
Cabinet Color	flat black	
Screen Size	27.5" diagonal	
Display Resolution	1366 x 768	
Brightness (typical)	280 cd/m ²	
Viewing Angle	170° × 160°	
Response Time (typical	l) 5 ms	
Broadcast System	NTSC/ATSC/QAM	
Max Audio Output	2 x 3 W	
Pro:Idiom	Yes	
VESA Standard	100 mm x 100 mm	
Power Supply	AC 115V~ 60Hz	
Power Consumption	33 W	
Standby Consumption	<1 W	
TV w/o Stand (WxHxD)	25.2 x 15.4 x 2.9"	
Set Weight	7.94 lbs.	
Shipping Weight	11.02 lbs.	

J32HE840 - 32" LED HDTV		
Cabinet Color	flat black	
Screen Size	31.5" diagonal	
Display Resolution	1366 x 768	
Brightness (typical)	280 cd/m ²	
Viewing Angle	178° × 178°	
Response Time (typical	al) 6.5 ms	
Broadcast System	NTSC/ATSC/QAM	
Max Audio Output	2 x 3 W	
Pro:Idiom	Yes	
VESA Standard	100 mm x 100 mm	
Power Supply	AC 100-240V 60Hz	
Power Consumption	52 W	
Standby Consumption	<1 W	
TV w/o Stand (WxHxD) 28.8 x 17.5 x 3.1"	
Set Weight	12.8 lbs.	
Shipping Weight	18.4 lbs.	

J42HE841 - 42" LED HDTV		
Cabinet Color	flat black	
Screen Size	42" diagona	
Display Resolution	1920 x 1080	
Brightness (typical)	300 cd/m	
Viewing Angle	178° × 178°	
Response Time (typica	al) 6 ms	
Broadcast System	NTSC/ATSC/QAM	
Max Audio Output	2 x 5 W	
Pro:Idiom	Yes	
VESA Standard	200 mm x 200 mm	
Power Supply	AC 115V~ 60Hz	
Power Consumption	80 W	
Standby Consumption	<1 W	
TV w/o Stand (WxHxD)) 38.8 x 23.5 x 2.9'	
Set Weight	24.25 lbs	
Shipping Weight	30.42 lbs	


Thin cabinet, reduced weight, set lays closer to the wall when mounted
Allows channels to have individual customized names
Sets the input/channel for the TV to tune when turned on
Sets the minimum, maximum and initial volume settings when the TV is turned on
Allows duplication of TV configuration for easy installation
Allows guests to play MP3 and view JPG files, as well as charge mobile devices
Allows the TV to turn off after a selectable period of inactivity
Separate remotes for configuration and operation
Disables front panel and menu controls to make television "tamper-proof"
Sets recurring time for the TV to power on and off
Auto power-off, less than 1 watt in standby mode, low power LED, no signal power-off
Wall-mount your TV using standard mounts
Allows control of an external device without the need for direct line of sight

Pillow Speaker Control	Pillow speaker interface allows connection to most brands and types of pillow speakers.
DVD Pillow Speaker Control	Optional DVD player that can be controlled by a pillow speaker.
ATSC Tuning Mode	Select between physical or virtual channel numbers, giving your headend distribution system optimal flexibility
Antenna/Cable Merge	Ability to merge antenna and cable channels into a single channel line-up
Auto Detect Side A/V	Allows users to easily connect peripheral devices to side input without use of remote
Last Power Mode	Selectable power state of the TV after a power cycle
Control Port	RS-232C control port allows for integration with "infotainment" providers and video conferencing equipment
Accessories	

7.0000001.00	
User Remote (KM3802)	Not Included (Optional)
Master Remote (KM3801)	Not Included (Optional)
Direct TV DRE Kit	Not Included (Optional)
Security Lock Kit	Not Included (Optional)
Certifications	
FCC, RoHS, Healthcare UL, CEC	Yes

Service/Limited Warranty Limited Warranty Two-Year replacement, provides for minimal downtime by offering advance replacement shipping instead of on-site repair

Note: Features and specifications are subject to change without notice.



Bed 1/2/3 Capable

Bezel Design for 28", 42" Models





Configuration for 28", 32", 42" Models







Configuration for 22" Model



EMERGY

GUIDE

© 2014