# PRO:IDIOM HOSPITALITY TELEVISION



# **SIZES | MODEL**



40" Bez	el. Be	zels vary based on model.	
40"		J40PT1440	
43"	$\mathbf{I}$	J43PT1440	
49"		J49PT1440	
55"		J55PT1440	

# **BRAND NEW!**

# **PT SERIES**

# Introducting the First RCA 4K Pro:Idiom Televisions!

Introducing RCA's first line of 4K Televisions, the new PT Series Televisions (released 2020). The PT Series builds upon the successes of RCAs LV Series TVs. Upgrading key hospitality-specific features to improve guest entertainment experience. Our 4K Pro:Idiom Enabled TVs give you the power to show your guests the latest in 3rd-party entertainment & programming. Our PT series works with all major 3rd party-content providers like DirecTV, COX, ENSEO, Dish Network and more. Backed by RCAs industry leading 2 Year, advanced replacement warranty. Upgrade your TVs to 4K Today!

## Accessories

R230D1A

# **Guest Remote Anti-Theft Swivel Stand Master Remote**

**FEATURES** 





































R230D2\*

Lockdown Plate may vary

<sup>\*</sup> Master remote R230D2, not included in standard TV box. Contact your RCA Sales rep to order.



### **SPECIFICATIONS PT SERIES**

Video         Screen Size (Diagonal)         39.75"         42.75"         48.59"         54.5"           Resolution         3840 x 2160 (4K)	Model	J40PT1440	J43PT1440	J49PT1440	J55PT1440
Resolution 3840 x 2160 (4K)  Digital Rights Management Pro:Idiom™  Type Direct-Lit LED  Brightness (Typical) 220 cd/m² 200 cd/m² 250 cd/m² 280 cd/m²  Response Time (Typical) 8 ms  Viewing Angle 178° x 178°  Frame Rate 60 Hz	Video				
Digital Rights Management Pro:Idiom™   Type Direct-Lit LED   Brightness (Typical) 220 cd/m² 200 cd/m² 250 cd/m² 280 cd/m²   Response Time (Typical) 8 ms   Viewing Angle 178° x 178°   Frame Rate 60 Hz	Screen Size (Diagonal)	39.75"	42.75"	48.59"	54.5"
Type Direct-Lit LED  Brightness (Typical) 220 cd/m² 200 cd/m² 250 cd/m² 280 cd/m²  Response Time (Typical) 8 ms  Viewing Angle 178° x 178°  Frame Rate 60 Hz	Resolution	3840 x 2160 (4K)			
Brightness (Typical)         220 cd/m²         200 cd/m²         250 cd/m²         280 cd/m²           Response Time (Typical)         8 ms           Viewing Angle         178° x 178°           Frame Rate         60 Hz	Digital Rights Management	Pro:ldiom™			
Response Time (Typical)  Viewing Angle  178° x 178°  Frame Rate  60 Hz	Туре	Direct-Lit LED			
Viewing Angle 178° x 178° Frame Rate 60 Hz	Brightness (Typical)	220 cd/m <sup>2</sup>	200 cd/m <sup>2</sup>	250 cd/m <sup>2</sup>	280 cd/m <sup>2</sup>
Frame Rate 60 Hz	Response Time (Typical)	8 ms			
	Viewing Angle	178° x 178°			
Tuners ATSC	Frame Rate	60 Hz			
	Tuners	ATSC			
UPC 811635022196 811635023100 811635022219 811635023117	UPC	811635022196	811635023100	811635022219	811635023117

Audio	
Audio Output / Speaker	10W + 10W / 2CH
Sound Modes	6 Modes (Standard, Music, Movie, Sports, News, Manual)
Dolby Digital Decoder™	Yes
Volume Limiter Feature	Yes

Power					
Typical (Watts)	< 63 W < 95 W <113 W				
Standby (Watts)	< 1 W				
Power Supply	AC 100V - 240V, 60 Hz				
Power Cable	5'6" Detachable Power Cable				

Dimensions				
VESA (mm)	200 mm x 200 mm		400 mm x 200 mm	
VESA™ Screw Size	М6			
Swivel	Anti-Theft Swivel			
TV ( W× H× D)	36.65" × 21.65" × 3.4"	38.5" x 22.75" x 3.5"	43.76" × 25.64" × 3.43"	49.125" × 28.125" × 3.5"
TV & Stand ( W×H×D)	36.65" × 23.75" × 7.25"	38.5" x 24.75" x 9"	43.76" × 27.8" × 9.16"	49.125" x 30.5" x 9"
Weight (lbs.)	14.61 lbs	16.10 lbs	21.12 lbs	29.5 lbs
Shipping Size ( W×H×D)	39.75" × 26" × 6.5"	41.75" x 26.25" x 6.5"	46.75" × 30.5" × 7"	55" x 32.125" x 7"
Shipping Weight (lbs.)	20.52 lbs	23.3 lbs	27.15 lbs	39.1 lbs

# Connectivity **Panels** (Side Panel, Bottom Panel) Side Panel | 1. HDMI 2 (ARC) 2. HDMI 3 3. YPbPr (Mini) 4. AV Input (Mini) 5. RF 6. Line Out Bottom Panel | 1. MTI In 2. RS232 3. IR Pass Through 4. COAX 5. HDMI 1 Ports (L to R)

## Certifications













## WARNING



This product can expose you to chemicals including lead, which is known to the state of California to cause cancer and birth defects or other reproductive harm. Wash hands after

For more information go to www.P65Warnings.ca.gov